



BEAMZ
MADE
EAZY

150.616 V1.3

HELIOS

QUICK START GUIDE

CONTROL MENU

MENU		DESCRIPTION		
ADDRESS	001-512	Address code settings		
CHANNEL	2CH	2-channel mode		
	6CH	6-channel mode		
	8CH	8-channel mode		
	11CH	11-channel mode		
DMX FAIL	Blackout	Control panel data blackout		
	Hold	Control panel data retention		
FREQUENCY	600HZ	600 refresh rate		
	1200HZ	1200 refresh rate		
	2000HZ	2000 refresh rate		
	4000HZ	4000 refresh rate		
	12KHZ	12K refresh rate		
	25KHZ	25K refresh rate		
CUSTOM	Red: 000-255	Red manual dimming		
	Green: 000-255	Green manual dimming		
	Blue: 000-255	Blue manual dimming		
	White: 000-255	White manual dimming		
	Amber: 000-255	Amber manual dimming		
	UV: 000-255	UV manual dimming		
PROGRAM	Static	Colour:01-32	32 static color blends	
		Speed:00-16	Strobe speed (when the speed is 00, it is a static color mixing)	
	Auto	Speed:01-16	Color jump	
	Fade	Fade 01	Speed:01-16	Color gradient
		Fade 02	Speed:01-16	Color mutant
		Fade 03	Speed:01-16	Color pulse
	CCT	2000K	Color temperature 2000K	
		2200K	Color temperature 2200K	
		2400K	Color temperature 2400K	
		2600K	Color temperature 2600K	
		2800K	Color temperature 2800K	
		3200K	Color temperature 3200K	
		3600K	Color temperature 3600K	
		4000K	Color temperature 4000K	
		4400K	Color temperature 4400K	
		4800K	Color temperature 4800K	
		5200K	Color temperature 5200K	
		5600K	Color temperature 5600K	
		6000K	Color temperature 6000K	
		6400K	Color temperature 6400K	
		6800K	Color temperature 6800K	
		7200K	Color temperature 7200K	
		7600K	Color temperature 7600K	
		8000K	Color temperature 8000K	
		8400K	Color temperature 8400K	
		8800K	Color temperature 8800K	
		9200K	Color temperature 9200K	
		9600K	Color temperature 9600K	
		10000K	Color temperature 10000K	

	WiFi	LED_XXX		WIFI mode and link address
WIRELESS DMX	ON	RD Protocol	On	Wireless on
			Clear	Clear former data
			Connect	Connect with slaves
			Off	Wireless off
			Receive	Receive (slave - status light is on white)
			Transmit	Send (Master - status light is blue)
		GZ Protocol	On / Off	Group ID 1.2.3.4.5.6.7
RUN TIME	2/4/6/8 hour			Lighting fixture usage time setting
BACK LIGHT	Always on			Display on
	10s			Display standby for 10 seconds, screen off
	20s			Display standby for 20 seconds, screen off
	30s			Display standby for 30 seconds, screen off
RF	ON/OFF			Remote control on/off
MENU LOCK	ON/OFF			Key lock on/off (When locking the screen, long press the UP+DOWN key to unlock)
FACTORY RESET	NO/YES			System self-test reset
CURVE	Led Curve 1			Linear curve
	Led Curve 2			Square curve
	Led Curve 3			Logarithmic curve
	Led Curve 4			S-curve
INFORMATION	Version	Vxxx		Software version
	Current Time	00H00M00S		Time used
	Temperature	xx°C		Current temperature
	RDM	ID xxx		RDM ID number

DMX CHANNELS

2 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	DIMMING	000-255	Total dimming
		000-010	Off light
		011-020	Color temperature 2000K
		021-030	Color temperature 2200K
		031-040	Color temperature 2400K
		041-050	Color temperature 2600K
		051-060	Color temperature 2800K
		061-070	Color temperature 3200K
		071-080	Color temperature 3600K
		081-090	Color temperature 4000K
		091-100	Color temperature 4400K
		101-110	Color temperature 4800K
2	COLOR TEMPERATURE	111-120	Color temperature 5200K
		121-130	Color temperature 5600K
		131-140	Color temperature 6000K
		141-150	Color temperature 6400K
		151-160	Color temperature 6800K
		161-170	Color temperature 7200K
		171-180	Color temperature 7600K
		181-190	Color temperature 8000K
		191-200	Color temperature 8400K
		201-210	Color temperature 8800K
		211-220	Color temperature 9200K
		221-230	Color temperature 9600K
		231-240	Color temperature 10000K
		241-255	No function

6 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	DIMMING	000-255	Red linear dimming
2		000-255	Green linear dimming
3		000-255	Blue linear dimming
4		000-255	White linear dimming
5		000-255	Amber linear dimming
6		000-255	UV linear dimming

8 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	DIMMING	000-255	Total dimming
		000-009	Off light
2		010-255	Strobe (slow to fast)
		000-255	Red linear dimming
3		000-255	Green linear dimming
		000-255	Blue linear dimming
4		000-255	White linear dimming
		000-255	Amber linear dimming
5		000-255	UV linear dimming
		000-255	

11 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	DIMMING	000-255	Total dimming
2		000-255	Red linear dimming
3		000-255	Green linear dimming
4		000-255	Blue linear dimming
5		000-255	White linear dimming
6		000-255	Amber linear dimming
7		000-255	UV linear dimming
8	STROBE	000-009	Off light
		010-255	Strobe (slow to fast)
9	COLOR TEMPERATURE	000-010	Off light
		011-020	Color temperature 2000K
		021-030	Color temperature 2200K
		031-040	Color temperature 2400K
		041-050	Color temperature 2600K
		051-060	Color temperature 2800K
		061-070	Color temperature 3200K
		071-080	Color temperature 3600K
		081-090	Color temperature 4000K
		091-100	Color temperature 4400K
		101-110	Color temperature 4800K
		111-120	Color temperature 5200K
		121-130	Color temperature 5600K
		131-140	Color temperature 6000K
		141-150	Color temperature 6400K
		151-160	Color temperature 6800K
		161-170	Color temperature 7200K
		171-180	Color temperature 7600K
		181-190	Color temperature 8000K
		191-200	Color temperature 8400K
		201-210	Color temperature 8800K
		211-220	Color temperature 9200K
		221-230	Color temperature 9600K
		231-240	Color temperature 10000K
		241-255	No function
10	MODE	000-009	OFF light
		010-050	Static color mixing
		051-100	Jump Mode
		101-150	Gradient mode
		151-200	Mutation pattern
		201-255	No function
11	SPEED	000-255	Speed







BEAMZ

YOUR FUTURE
YOUR SKILLS
YOUR PLATFORM
YOUR PARTY
YOUR EVENT

 **beamZ^{Pro}**

offers a wide range of high performance lighting equipment and related accessories for the rental, entertainment and architectural lighting markets. BeamZ Pro stands for performance, innovation and value pricing!



BEAMZLIGHTING.COM